



DHL Sweden

DHL QuotePrice
Web Service Specification
Version 7.2

Updated 2016-05-16

Version history

Datum/version	Typ	Kommentar	Uppdat. av	Källa
2008-02-07 / Version 1.0	New document	New document.	Katharina Kronlund	Pdb
2008-05-05 / Version 2.0	QuotePrice SE	The document is extended with information about QuotePrice for Swedish products.	Katharina Kronlund	Pdb
2008-06-24 / Version 3.0	QuotePrice EC	The document is extended with information about QuotePrice for the product EuroConnect.	Katharina Kronlund	Pdb
2008-08-13 / Version 3.1	Example	Added example of the SOAP:Envelope for the request.	Katharina Kronlund	Pdb
2011-10-06 / Version 4.0	Schema	Changed schema information, new options available.	Katharina Kronlund	Pdb
2013-03-08 / Version 5.0	New products	The document is extended with information about QuotePrice for the product DHLB2C, DHLC2B, DkEuroConnect, DkEuroConnectDomestic, DkEuroLineDomestic, DHLExpress	Daniel Arbin	Pdb
2013-10-15 / Version 6.0	New product	Added HomeDelivery information	Daniel Arbin	Pdb
2014-01-30 / Version 7.0	Schema	Added new options for HomeDelivery	Daniel Arbin	Pdb
2016-02-25 / Version 7.1	URL update	Updated URL for TEST Removed obsolete remark about unavailable addresses in the WSDL.	Peter Karlsson	DHL
2016-02-25 / Version 7.2	URL update	Updated URL for PROD	Peter Karlsson	DHL

DHL QuotePrice – Web Service Specification

1	Summary	5
2	Document versioning and status	5
3	General	5
3.1	Public endpoints	5
3.2	Security	5
3.3	Error Handling	5
4	DHL QuotePrice operations	6
4.1	QuoteForPrice / QuoteForPriceForModuleCountry operation	6
4.1.1	QuoteForPrice Request	6
4.1.2	QuoteForPriceForModuleCountry Request	6
4.1.3	QuoteForPrice Response	6
4.1.4	XML schema for Credentials	7
4.1.5	XML schema for Quote	7
4.1.6	XML schema for PriceResponse	7
4.2	GetQuotableAccount / GetQuotableAccountForModuleCountry operation	8
4.2.1	GetQuotableAccount Request	8
4.2.2	GetQuotableAccountForModuleCountry Request	8
4.2.3	GetQuotableAccount Response	9
4.2.4	XML schema for Credentials	9
4.2.5	XML schema for QuotableAccountResponse	9
5	Types	10
5.1	Credentials	10
5.2	tQuote	10
5.2.1	XML schema for NorsklInnland	11
5.2.2	XML schema for DHLStycke	13
5.2.3	XML schema for DHLParti	15
5.2.4	XML schema for DHLPall	17
5.2.5	XML schema for DHLPaket (EuropremiumSE)	19
5.2.6	XML schema for Swednet	20
5.2.7	XML schema for SverigePall	22
5.2.8	XML schema for DHLEconomySelect (DHLEuroplus)	23

5.2.9	XML schema for DHLEuropack.....	24
5.2.10	XML schema for EuroConnect	25
5.2.11	XML schema for DHLB2C.....	29
5.2.12	XML schema for DHLC2B.....	30
5.2.13	Xml schema for DkEuroConnect.....	31
5.2.14	Xml schema for DkEuroConnectDomestic.....	35
5.2.15	Xml schema for DkEuroLineDomestic.....	39
5.2.16	Xml schema for DHLExpress	42
5.2.17	XML schema for DHLHomeDeliveryDHLTerminal (Product 401).....	44
5.2.18	XML schema for DHLHomeDeliveryDHLTerminalReturn (Product 402).....	46
5.2.19	XML schema for DHLHomeDeliveryExternalTerminal (Product 501).....	47
5.2.20	XML schema for DHLHomeDeliveryExternalTerminalReturn (Product 502).....	49
5.2.21	XML schema for General	51
6	Request example	54
6.1	DHLStycke SOAP:Envelope	54
6.2	DHLHomeDeliveryExternalTerminal SOAP:Envelope example	55

1 Summary

This document describes how to communicate with the web service DHL QuotePrice. Target audience is integrators and system developers who will call and use the service.

2 Document versioning and status

This document will be versioned with a version number. Changes will be described in short in the Version history section.

3 General

The service is implemented using VB.NET 2005 and published as a Web Service.

3.1 Public endpoints

There's a test and a production version of the service. The table below shows the current URL's to the service.

TEST	https://www.dhltoolboxtest.se/DHLQuotePriceWS/QuotePrice.asmx
PRODUCTION	https://www.dhltoolbox.se/DHLQuotePriceWS/QuotePrice.asmx

The WSDL for each service can be retrieved by appending “?wsdl” at the end of the URL.

3.2 Security

The access to the web service will be restricted using Basic Authentication. User name and Password is sent as part of the HTTP request header

There is also a data access check using a passed user name and password. Depending on the user name and password different functions in the web service may be accessible. User name and password will be sent in clear text from the client to the service.

3.3 Error Handling

Errors will be encapsulated as exceptions. All errors will be logged by the service.

4 DHL QuotePrice operations

DHL QuotePrice Service manages requests of price information from the main frame. This section describes the operations exposed by the service.

4.1 QuoteForPrice / QuoteForPriceForModuleCountry operation

Two operations are available to get price information. The original QuoteForPrice or the new QuoteForPriceForModuleCountry, where the only difference is that QuoteForPriceForModuleCountry takes country code as an additional parameter.

Request:

QuoteForPrice Request



Response:

QuoteForPrice Response

4.1.1 QuoteForPrice Request

Parameter	Message part	Required / Cardinality	Type / Length	Description
Credentials	Body	Yes	Credentials	An object of the class Service.Entities.Credentials
Quote	Body	Yes	tQuote	An object of the class Service.Entities.tQuote

4.1.2 QuoteForPriceForModuleCountry Request

Parameter	Message part	Required / Cardinality	Type / Length	Description
Credentials	Body	Yes	Credentials	An object of the class Service.Entities.Credentials
Quote	Body	Yes	tQuote	An object of the class Service.Entities.tQuote
strCountryCode	Body	Yes	String	A country code used by the service to get different configurations. Only "DK" is configured except the default configuration.

4.1.3 QuoteForPrice Response

Parameter	Message	Type /	Description
-----------	---------	--------	-------------

	part	Length	
PriceResponse	Body	PriceResponse	An object of the class Service.Entities.PriceResponse

4.1.4 XML schema for Credentials

```
<xs:element name="Credentials">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element name="User" type="xs:string" maxOccurs="1" minOccurs="1" />  
      <xs:element name="Password" type="xs:string" maxOccurs="1" minOccurs="1" />  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

4.1.5 XML schema for Quote

```
<xs:element name="Quote" type="tQuote" />  
<xs:complexType name="tQuote">  
  <xs:sequence>  
    <xs:choice id="Product" maxOccurs="1" minOccurs="1">  
      <xs:element name="NorskInnland" type="tNorskInnland" />  
      <xs:element name="DHLStycke" type="tDHLStycke" />  
      <xs:element name="DHLParti" type="tDHLParti" />  
      <xs:element name="DHLPall" type="tDHLPall" />  
      <xs:element name="EuropremiumSE" type="tEuropremiumSE" />  
      <xs:element name="DHLB2C" type="tDHLB2C" />  
      <xs:element name="DHLC2B" type="tDHLC2B" />  
      <xs:element name="Swednet" type="tSwednet" />  
      <xs:element name="SverigePall" type="tSverigePall" />  
      <xs:element name="DHLEuroplus" type="tDHLEuroplus" />  
      <xs:element name="DHLEuropack" type="tDHLEuropack" />  
      <xs:element name="EuroConnect" type="tEuroConnect" />  
      <xs:element name="DkEuroConnect" type="tDkEuroConnect" />  
      <xs:element name="DkEuroConnectDomestic" type="tDkEuroConnectDomestic" />  
      <xs:element name="DkEuroLineDomestic" type="tDkEuroLineDomestic" />  
      <xs:element name="DHLExpress" type="tDHLExpress" />  
      <xs:element name="DHLHomeDeliveryDhlTerminal" type="tDHLHomeDeliveryDhlTerminal" />  
      <xs:element name="DHLHomeDeliveryDhlTerminalReturn" type="tDHLHomeDeliveryDhlTerminalR  
eturn" />  
      <xs:element name="DHLHomeDeliveryExternalTerminal" type="tDHLHomeDeliveryExternalTermi  
nal" />  
      <xs:element name="DHLHomeDeliveryExternalTerminalReturn" type="tDHLHomeDeliveryExterna  
lTerminalReturn" />  
    </xs:choice>  
  </xs:sequence>  
</xs:complexType>
```

4.1.6 XML schema for PriceResponse

```
<xs:element name="PriceResponse">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element name="ResponseRow" maxOccurs="unbounded">  
        <xs:complexType>
```

```

<xs:sequence>
  <xs:element name="Id" type="xs:string" />
  <xs:element name="Description" type="xs:string" />
  <xs:element name="DescriptionEng" type="xs:string" />
  <xs:element name="Value" type="xs:string" />
  <xs:element name="Unit" type="xs:string" />
  <xs:element name="SortOrder" type="xs:int" />
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

4.2 GetQuotableAccount / GetQuotableAccountForModuleCountry operation

The operation gets information about quotable accounts.

Two operations are available to get information about quotable accounts. The original GetQuotableAccount or the new GetQuotableAccountForModuleCountry, where the only difference is that GetQuotableAccountForModuleCountry takes country code as an additional parameter.

Request:

GetQuotableAccount Request



Response:

GetQuotableAccount Response

4.2.1 GetQuotableAccount Request

Parameter	Message part	Required / Cardinality	Type / Length	Description
Credentials	Body	Yes	Credentials	An object of the class Service.Entities.Credentials
strUser	Body	Yes	String	User name

4.2.2 GetQuotableAccountForModuleCountry Request

Parameter	Message part	Required / Cardinality	Type / Length	Description
Credentials	Body	Yes	Credentials	An object of the class Service.Entities.Credentials
strUser	Body	Yes	String	User name

strCountryCode	Body	Yes	String	A country code used by the service to get different configurations. Only "DK" is configured except the default configuration.
----------------	------	-----	--------	---

4.2.3 GetQuotableAccount Response

Parameter	Message part	Type / Length	Description
QuotableAccountResponse	Body	QuotableAccountResponse	An object of the class Service.Entities.QuotableAccountResponse

4.2.4 XML schema for Credentials

```
<xs:element name="Credentials">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="User" type="xs:string" maxOccurs="1" minOccurs="1" />
      <xs:element name="Password" type="xs:string" maxOccurs="1" minOccurs="1" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

4.2.5 XML schema for QuotableAccountResponse

```
<xs:element name="QuotableAccountResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="QAResponseRow" maxOccurs="unbounded">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="AgreementNo" type="xs:string" />
            <xs:element name="Product" type="tProduct" maxOccurs="unbounded"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="tProduct">
  <xs:sequence>
    <xs:element name="ProductCode" type="xs:string" maxOccurs="1" minOccurs="1" />
    <xs:element name="ProductDescription" type="xs:string" maxOccurs="1" minOccurs="1" />
  </xs:sequence>
</xs:complexType>
```

5 Types

5.1 Credentials

Attribute	Required / Cardinality	Type / Length	Description
User	Yes	String	Contact DHL Support Desk for user name and password.
Password	Yes	String	Contact DHL Support Desk for user name and password.

5.2 tQuote

Attribute	Required / Cardinality	Type / Length	Description
NorsklInnland	Choice	tNorsklInnland NOTE! This type was tQuoteNorsklInnland in the earlier versions of this service!	Quote price for the product NorsklInnland.
DHLStycke	Choice	tDHLStycke	Quote price for the product DHLStycke.
DHLParti	Choice	tDHLParti	Quote price for the product DHLParti.
DHLPall	Choice	tDHLPall	Quote price for the product DHLPall.
EuropremiumSE	Choice	tEuropremiumSE	Quote price for the product EuropremiumSE.
Swednet	Choice	tSwednet	Quote price for the product Swednet.
SverigePall	Choice	tSverigePall	Quote price for the product SverigePall.
DHLEuroplus	Choice	tDHLEuroplus	Quote price for the product DHLEuroplus.
DHLEuropack	Choice	tDHLEuropack	Quote price for the product DHLEuropack.
EuroConnect	Choice	tEuroConnect	Quote price for the product EuroConnect.

5.2.1 XML schema for NorsklInnland

```
<xs:complexType name="tNorskInnland">
  <xs:sequence>
    <xs:element name="FromPostCode" type="tPostalCode_NO" maxOccurs="1" minOccurs="1" />
    <xs:element name="ToPostCode" type="tPostalCode_NO" maxOccurs="1" minOccurs="1" />
    <xs:element name="FreightPayer" type="tFreightPayer" maxOccurs="1" minOccurs="1" />
    <xs:element name="AgreementNo" type="tAgreementNo" maxOccurs="1" minOccurs="1" />
    <xs:element name="RegistrationDate" type="xs:date" maxOccurs="1" minOccurs="1" />
    <xs:element name="Weight" type="tWeightNO" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="tVolumeNO" maxOccurs="1" minOccurs="0" />
    <xs:element name="Loadingmeter" type="tLoadingmeterNO" maxOccurs="1" minOccurs="0" />
    <xs:element name="NoItems" type="tNoItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="NoPallets" type="tNoPallets" maxOccurs="1" minOccurs="0" />
    <xs:element name="DangerousOrWarm" type="tDangerousOrWarm" maxOccurs="1" minOccurs="1" />
    <xs:element name="CODAmount" type="tCODAmount" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="tPostalCode_NO">
  <xs:restriction base="xs:string">
    <xs:pattern value="\d{4}" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tFreightPayer">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="Sender" />
    <xs:enumeration value="Receiver" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tAgreementNo">
  <xs:restriction base="xs:string">
    <xs:pattern value="\d{6}" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightValueNO">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="30000" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightUnitNO">
  <xs:restriction base="xs:string">
    <xs:enumeration value="kg" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWeightNO">
  <xs:simpleContent>
    <xs:extension base="tWeightValueNO">
      <xs:attribute name="unit" type="tWeightUnitNO" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValueNO">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0.1" />
    <xs:maxInclusive value="999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tVolumeUnitNO">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m3" />
  </xs:restriction>
</xs:simpleType>
```

```

</xs:simpleType>
<xs:complexType name="tVolumeNO">
  <xs:simpleContent>
    <xs:extension base="tVolumeValueNO">
      <xs:attribute name="unit" type="tVolumeUnitNO" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValueNO">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0.1" />
    <xs:maxInclusive value="99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tLoadingmeterUnitNO">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeterNO">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValueNO">
      <xs:attribute name="unit" type="tLoadingmeterUnitNO" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tNoItems">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="99999" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoPallets">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="99999" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tDangerousOrWarm">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="None" />
    <xs:enumeration value="Dangerous" />
    <xs:enumeration value="Warm" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCODValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="9999999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCODAmount">
  <xs:simpleContent>
    <xs:extension base="tCODValue">
      <xs:attribute name="currency" use="required">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:enumeration value="NOK" />
          </xs:restriction>
        </xs:simpleType>
      </xs:attribute>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

```

```
</xs:simpleContent>  
</xs:complexType>
```

5.2.2 XML schema for DHLStycke

```
<xs:complexType name="tDHLStycke">  
  <xs:sequence>  
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />  
    <xs:element name="Weight" type="DHLStycke:tWeight1" maxOccurs="1" minOccurs="0" />  
    <xs:element name="Volume" type="DHLStycke:tVolume1" maxOccurs="1" minOccurs="0" />  
    <xs:element name="Loadingmeter" type="DHLStycke:tLoadingmeter1" maxOccurs="1"  
minOccurs="0" />  
    <xs:element name="LongGoods" type="DHLStycke:tLongGoods1" maxOccurs="1" minOccurs="0" />  
    <xs:element name="SenderReceiver" type="DHLStycke:tSenderReceiver1" maxOccurs="1"  
minOccurs="1" />  
    <xs:element name="Values" type="DHLStycke:tValues1" maxOccurs="1" minOccurs="0" />  
    <xs:element name="Options" type="DHLStycke:tOptions1" maxOccurs="1" minOccurs="0" />  
  </xs:sequence>  
</xs:complexType>
```

DHLStycke:

```
<xs:complexType name="tWeight1">  
  <xs:simpleContent>  
    <xs:extension base="tWeightValue">  
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />  
    </xs:extension>  
  </xs:simpleContent>  
</xs:complexType>  
<xs:simpleType name="tWeightValue">  
  <xs:restriction base="xs:decimal">  
    <xs:minInclusive value="1" />  
    <xs:maxInclusive value="2500" />  
    <xs:fractionDigits value="2" />  
  </xs:restriction>  
</xs:simpleType>  
<xs:complexType name="tWeightLG">  
  <xs:simpleContent>  
    <xs:extension base="tWeightValueLG">  
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />  
    </xs:extension>  
  </xs:simpleContent>  
</xs:complexType>  
<xs:simpleType name="tWeightValueLG">  
  <xs:restriction base="xs:decimal">  
    <xs:minInclusive value="1" />  
    <xs:maxInclusive value="49.99" />  
    <xs:fractionDigits value="2" />  
  </xs:restriction>  
</xs:simpleType>  
<xs:complexType name="tVolume1">  
  <xs:simpleContent>  
    <xs:extension base="tVolumeValue">  
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />  
    </xs:extension>  
  </xs:simpleContent>  
</xs:complexType>  
<xs:simpleType name="tVolumeValue">  
  <xs:restriction base="xs:decimal">  
    <xs:minInclusive value="0" />  
    <xs:maxInclusive value="8.9" />  
    <xs:fractionDigits value="3" />  
  </xs:restriction>  
</xs:simpleType>  
<xs:complexType name="tLoadingmeter1">
```

```
<xs:simpleContent>
  <xs:extension base="tLoadingmeterValue" />
</xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="1.3" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLongGoods1">
  <xs:sequence>
    <xs:element name="Weight" type="tWeightLG" maxOccurs="1" minOccurs="1" />
    <xs:element name="Length" type="tLength1" maxOccurs="1" minOccurs="1" />
    <xs:element name="Width" type="tWidth1" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tLength1">
  <xs:simpleContent>
    <xs:extension base="tLengthValue">
      <xs:attribute name="unit" type="General:tLengthUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="3.00" />
    <xs:maxInclusive value="5.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth1">
  <xs:simpleContent>
    <xs:extension base="tWidthValue">
      <xs:attribute name="unit" type="General:tWidthUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="2.40" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver1">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues1">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="NoOfEURPallets" type="General:tNoOfEURPallets" maxOccurs="1"
minOccurs="0" />
    <xs:element name="CODAmount" type="General:tCODAmountSE" maxOccurs="1" minOccurs="0" />
    <xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
    <xs:element name="PalletPlace" type="General:tPalletPlace" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

```
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="tOptions1">
    <xs:sequence>
      <xs:element name="Dangerous" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
      <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="PreAdviceComType" type="General:tComType" maxOccurs="1" minOccurs="0"
/>
      <xs:element name="DeliveryAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0"
/>
      <xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
      <xs:element name="Warm" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
      <xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="LQ_DangerousGoods" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="DeliveryWithoutPOD" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
      <xs:element name="PickupAtTerminal" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    </xs:sequence>
  </xs:complexType>
```

5.2.3 XML schema for DHLParti

```
  <xs:complexType name="tDHLParti">
    <xs:sequence>
      <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
      <xs:element name="Weight" type="DHLParti:tWeight2" maxOccurs="1" minOccurs="0" />
      <xs:element name="Volume" type="DHLParti:tVolume2" maxOccurs="1" minOccurs="0" />
      <xs:element name="Loadingmeter" type="DHLParti:tLoadingmeter2" maxOccurs="1"
minOccurs="0" />
      <xs:element name="LongGoods" type="DHLParti:tLongGoods2" maxOccurs="1" minOccurs="0" />
      <xs:element name="SenderReceiver" type="DHLParti:tSenderReceiver2" maxOccurs="1"
minOccurs="1" />
      <xs:element name="Values" type="DHLParti:tValues2" maxOccurs="1" minOccurs="0" />
      <xs:element name="Options" type="DHLParti:tOptions2" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
  </xs:complexType>
```

DHLParti:

```
  <xs:complexType name="tWeight2">
    <xs:simpleContent>
      <xs:extension base="tWeightValue">
        <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tWeightValue">
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="1" />
      <xs:maxInclusive value="99999" />
      <xs:fractionDigits value="2" />
    </xs:restriction>
  </xs:simpleType>
```

```
<xs:complexType name="tVolume2">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="357.00" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeter2">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="51.00" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLongGoods2">
  <xs:sequence>
    <xs:element name="Weight" type="tWeight2" maxOccurs="1" minOccurs="1" />
    <xs:element name="Length" type="tLength2" maxOccurs="1" minOccurs="1" />
    <xs:element name="Width" type="tWidth2" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tLength2">
  <xs:simpleContent>
    <xs:extension base="tLengthValue">
      <xs:attribute name="unit" type="General:tLengthUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="3.00" />
    <xs:maxInclusive value="12.00" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth2">
  <xs:simpleContent>
    <xs:extension base="tWidthValue">
      <xs:attribute name="unit" type="General:tWidthUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="2.40" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver2">
  <xs:sequence>
```



```
<xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
<xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
<xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
<xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>
<xs:complexType name="tValues2">
<xs:sequence>
<xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
<xs:element name="NoOfEURPallets" type="General:tNoOfEURPallets" maxOccurs="1"
minOccurs="0" />
<xs:element name="Sort" type="General:tSort" maxOccurs="1" minOccurs="0" />
<xs:element name="Quantity" type="General:tQuantity" maxOccurs="1" minOccurs="0" />
<xs:element name="CODAmount" type="General:tCODAmountSE" maxOccurs="1" minOccurs="0" />
<xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
<xs:element name="PalletPlace" type="General:tPalletPlace" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions2">
<xs:sequence>
<xs:element name="Dangerous" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="DeliveryAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0"
/>
<xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="Cold" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="Warm" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="LQ_DangerousGoods" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="DeliveryWithoutPOD" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="PickupAtTerminal" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
</xs:sequence>
</xs:complexType>
```

5.2.4 XML schema for DHLPal1

```
<xs:complexType name="tDHLPal1">
<xs:sequence>
<xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
<xs:element name="Weight" type="DHLPal1:tWeight3" maxOccurs="1" minOccurs="0" />
<xs:element name="SenderReceiver" type="DHLPal1:tSenderReceiver3" maxOccurs="1"
minOccurs="1" />
<xs:element name="Values" type="DHLPal1:tValues3" maxOccurs="1" minOccurs="0" />
<xs:element name="Options" type="DHLPal1:tOptions3" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>
```

DHLPal1:

```
<xs:complexType name="tWeight3">
<xs:simpleContent>
<xs:extension base="tWeightValue">
<xs:attribute name="unit" type="General:tWeightUnit" use="required" />
</xs:extension>
</xs:simpleContent>
</xs:complexType>
```

```
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="2500" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver3">
    <xs:sequence>
        <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
        <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
        <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues3">
    <xs:sequence>
        <xs:element name="NoOfFullPallets" type="General:tNoOfFullPallets" maxOccurs="1"
minOccurs="0" />
        <xs:element name="NoOfHalfPallets" type="General:tNoOfHalfPallets" maxOccurs="1"
minOccurs="0" />
        <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
        <xs:element name="NoOfEURPallets" type="General:tNoOfEURPallets" maxOccurs="1"
minOccurs="0" />
        <xs:element name="CODAmount" type="General:tCODAmountSE" maxOccurs="1" minOccurs="0" />
        <xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions3">
    <xs:sequence>
        <xs:element name="Dangerous" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
        <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="PreAdviceComType" type="General:tComType" maxOccurs="1" minOccurs="0"
/>
        <xs:element name="DeliveryAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0"
/>
        <xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="Warm" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="LQ_DangerousGoods" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="DeliveryWithoutPOD" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="PickupAtTerminal" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    </xs:sequence>
</xs:complexType>
```

5.2.5 XML schema for DHL Paket (EuropremiumSE)

```
<xs:complexType name="tEuropremiumSE">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="EuropremiumSE:tWeight4" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="EuropremiumSE:tVolume4" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="EuropremiumSE:tSenderReceiver4" maxOccurs="1"
minOccurs="1" />
    <xs:element name="Values" type="EuropremiumSE:tValues4" maxOccurs="1" minOccurs="0" />
    <xs:element name="Options" type="EuropremiumSE:tOptions4" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

EuropremiumSE:
<xs:complexType name="tWeight4">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="150" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume4">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="0.53" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver4">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues4">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions4">
  <xs:sequence>
    <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

```
<xs:element name="PreAdviceComType" type="General:tComType" maxOccurs="1" minOccurs="0"
/>
<xs:element name="DeliveryAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0"
/>
<xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="LQ_DangerousGoods" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="DeliveryWithoutPOD" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
<xs:element name="PickupAtTerminal" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
</xs:sequence>
</xs:complexType>
```

5.2.6 XML schema for Swednet

```
<xs:complexType name="tSwednet">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="Swednet:tWeight5" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="Swednet:tVolume5" maxOccurs="1" minOccurs="0" />
    <xs:element name="Loadingmeter" type="Swednet:tLoadingmeter5" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="LongGoods" type="Swednet:tLongGoods5" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="Swednet:tSenderReceiver5" maxOccurs="1"
minOccurs="1" />
    <xs:element name="Values" type="Swednet:tValues5" maxOccurs="1" minOccurs="0" />
    <xs:element name="Options" type="Swednet:tOptions5" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
Swednet:
<xs:complexType name="tWeight5">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="999" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume5">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
```

```

        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeter5">
    <xs:simpleContent>
        <xs:extension base="tLoadingmeterValue" />
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLongGoods5">
    <xs:sequence>
        <xs:element name="Weight" type="tWeight5" maxOccurs="1" minOccurs="1" />
        <xs:element name="Length" type="tLength5" maxOccurs="1" minOccurs="1" />
        <xs:element name="Width" type="tWidth5" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tLength5">
    <xs:simpleContent>
        <xs:extension base="tLengthValue">
            <xs:attribute name="unit" type="General:tLengthUnit" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="3.00" />
        <xs:maxInclusive value="12.00" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth5">
    <xs:simpleContent>
        <xs:extension base="tWidthValue">
            <xs:attribute name="unit" type="General:tWidthUnit" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="2.40" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver5">
    <xs:sequence>
        <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues5">
    <xs:sequence>
        <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
</xs:complexType>
    </xs:sequence>
</xs:complexType>

```

```

    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="NoOfEURPallets" type="General:tNoOfEURPallets" maxOccurs="1"
minOccurs="0" />
    <xs:element name="Sort" type="General:tSort" maxOccurs="1" minOccurs="0" />
    <xs:element name="Quantity" type="General:tQuantity" maxOccurs="1" minOccurs="0" />
    <xs:element name="CODAmount" type="General:tCODAmountSE" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions5">
  <xs:sequence>
    <xs:element name="Dangerous" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="Cold" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="Warm" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

```

5.2.7 XML schema for SverigePall

```

<xs:complexType name="tSverigePall">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="SverigePall:tWeight6" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="SverigePall:tSenderReceiver6" maxOccurs="1"
minOccurs="1" />
    <xs:element name="Values" type="SverigePall:tValues6" maxOccurs="1" minOccurs="1" />
    <xs:element name="Options" type="SverigePall:tOptions6" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
SverigePall:
<xs:complexType name="tWeight6">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="998" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver6">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

```

```
<xs:complexType name="tValues6">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="NoOfPallets" type="tNoOfPallets" maxOccurs="1" minOccurs="1" />
    <xs:element name="NoOfEURPallets" type="General:tNoOfEURPallets" maxOccurs="1"
minOccurs="0" />
    <xs:element name="CODAmount" type="General:tCODAmountSE" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions6">
  <xs:sequence>
    <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="tNoOfPallets">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="1" />
    <xs:enumeration value="2" />
  </xs:restriction>
</xs:simpleType>
```

5.2.8 XML schema for DHLEconomySelect (DHLEuroplus)

```
<xs:complexType name="tDHLEuroplus">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="DHLEuroplus:tWeight7" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="DHLEuroplus:tVolume7" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="DHLEuroplus:tSenderReceiver7" maxOccurs="1"
minOccurs="0" />
    <xs:element name="Values" type="DHLEuroplus:tValues7" maxOccurs="1" minOccurs="1" />
    <xs:element name="Options" type="DHLEuroplus:tOptions7" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

DHLEuroplus:

```
<xs:complexType name="tWeight7">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="2500" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume7">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

```
</xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="12" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver7">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues7">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="CODAmount" type="General:tCODAmountSE" maxOccurs="1" minOccurs="0" />
    <xs:element name="CountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
    <xs:element name="ToPostCodeInt" type="General:tToPostCodeInt" maxOccurs="1"
minOccurs="1" />
    <xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions7">
  <xs:sequence>
    <xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions8">
  <xs:sequence>
    <xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="ProdStretch" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    <xs:element name="ImportClearance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

5.2.9 XML schema for DHLEuropack

```
<xs:complexType name="tDHLEuropack">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="DHLEuropack:tWeight8" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="DHLEuropack:tSenderReceiver8" maxOccurs="1"
minOccurs="0" />
    <xs:element name="Values" type="DHLEuropack:tValues8" maxOccurs="1" minOccurs="1" />
    <xs:element name="Options" type="DHLEuropack:tOptions8" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

DHLEuropack:

```
<xs:complexType name="tWeight8">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
  </xs:restriction>
</xs:simpleType>
```



```
        <xs:maxInclusive value="31.5" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver8">
    <xs:sequence>
        <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
        <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues8">
    <xs:sequence>
        <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
        <xs:element name="CountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
        <xs:element name="ToPostCodeInt" type="General:tToPostCodeInt" maxOccurs="1"
minOccurs="1" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions8">
    <xs:sequence>
        <xs:element name="ImportClearance" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
    </xs:sequence>
</xs:complexType>
```

5.2.10 XML schema for EuroConnect

```
<xs:complexType name="tEuroConnect">
    <xs:sequence>
        <xs:element name="AgreementNo" type="EuroConnect:tAgreementNo_EC" maxOccurs="1"
minOccurs="0" />
        <xs:element name="SenderReceiver" type="EuroConnect:tSenderReceiver_EC" maxOccurs="1"
minOccurs="1" />
        <xs:element name="Dimensions" type="EuroConnect:tDimensions" maxOccurs="1" minOccurs="0"
/>
    </xs:sequence>
</xs:complexType>
```

EuroConnect:

```
<xs:complexType name="tSenderReceiver_EC">
    <xs:sequence>
        <xs:element name="ImportExport" type="tImportExport" maxOccurs="1" minOccurs="1" />
        <xs:element name="FromCountryCode" type="General:tCountryCode" maxOccurs="1"
minOccurs="1" />
        <xs:element name="FromPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1"
/>
        <xs:element name="ToPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tDimensions">
    <xs:sequence>
        <xs:element name="Weight" type="tWeight_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Volume" type="tVolume_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Loadingmeter" type="tLoadingmeter_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Length" type="tLength_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Width" type="tWidth_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Height" type="tHeight_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="tAgreementNo_EC">
    <xs:restriction base="xs:string">
        <xs:pattern value="\d{0,8}" />
    </xs:restriction>
</xs:simpleType>
```

```

    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tImportExport">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="I" />
    <xs:enumeration value="E" />
    <xs:enumeration value="D" />
    <xs:enumeration value="ED" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tPostalCode_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="6" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWeight_EC">
  <xs:simpleContent>
    <xs:extension base="tWeightValue_EC">
      <xs:attribute name="unit" type="tWeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue_EC">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999900" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="kg" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume_EC">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue_EC">
      <xs:attribute name="unit" type="tVolumeUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tVolumeUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeter_EC">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue_EC" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.9" />
    <xs:fractionDigits value="1" />
  </xs:restriction>
</xs:simpleType>

```

```

<xs:complexType name="tLength_EC">
  <xs:simpleContent>
    <xs:extension base="tLengthValue_EC">
      <xs:attribute name="unit" type="tLengthUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tLengthUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth_EC">
  <xs:simpleContent>
    <xs:extension base="tWidthValue_EC">
      <xs:attribute name="unit" type="tWidthUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWidthUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="cm" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tHeight_EC">
  <xs:simpleContent>
    <xs:extension base="tHeightValue_EC">
      <xs:attribute name="unit" type="tHeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tHeightValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tHeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="cm" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCombiterms_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCOD_EC">
  <xs:simpleContent>

```

```

        <xs:extension base="tCODValue_EC">
            <xs:attribute name="currency" type="tCODCurrency_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tCODValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCODCurrency_EC">
    <xs:restriction base="xs:string">
        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tInsurance_EC">
    <xs:simpleContent>
        <xs:extension base="tInsuranceValue_EC">
            <xs:attribute name="currency" type="tInsuranceCurrency_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tInsuranceValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tInsuranceCurrency_EC">
    <xs:restriction base="xs:string">
        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfPallets_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfItems_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999999" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tOptions9">
    <xs:sequence>
        <xs:element name="Combiterm" type="tCombiterms_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="COD" type="tCOD_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="DangerousGoods" type="xs:boolean" default="false" maxOccurs="1"
minOccurs="0" />
        <xs:element name="Insurance" type="tInsurance_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfPallets" type="tNoOfPallets_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfItems" type="tNoOfItems_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>

```

5.2.11 XML schema for DHLB2C

```
<xs:complexType name="tDHLB2C">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="EuropremiumSE:tWeight4" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="EuropremiumSE:tVolume4" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="EuropremiumSE:tSenderReceiver4" maxOccurs="1" min
Occurs="1" />
    <xs:element name="Values" type="EuropremiumSE:tValues4" maxOccurs="1" minOccurs="0" />
    <xs:element name="Options" type="EuropremiumSE:tOptions4" maxOccurs="1" minOccurs="0" />
    <xs:element name="OwnSurCharge" type="General:tOwnSurCharge" maxOccurs="1" minOccurs="0"
/>
  </xs:sequence>
</xs:complexType>
```

DhlB2C:

```
<xs:complexType name="tWeight4">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="150" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume4">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="0.535" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver4">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0"
/>
    <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" /
>
    <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues4">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions4">
```

```
<xs:sequence>
  <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
  <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
</xs:sequence>
<xs:element name="PreAdviceComType" type="General:tComType" maxOccurs="1" minOccurs="0" />
<xs:element name="DeliveryAdvice" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="LQ_DangerousGoods" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="DeliveryWithoutPOD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="PickupAtTerminal" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>
```

5.2.12 XML schema for DHLC2B

```
<xs:complexType name="tDHLC2B">
  <xs:sequence>
    <xs:element name="AgreementNo" type="General:tAgreementNo" maxOccurs="1" minOccurs="0" />
    <xs:element name="Weight" type="EuropremiumSE:tWeight4" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="EuropremiumSE:tVolume4" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="EuropremiumSE:tSenderReceiver4" maxOccurs="1" minOccurs="1" />
    <xs:element name="Values" type="EuropremiumSE:tValues4" maxOccurs="1" minOccurs="0" />
    <xs:element name="Options" type="EuropremiumSE:tOptions4" maxOccurs="1" minOccurs="0" />
    <xs:element name="OwnSurCharge" type="General:tOwnSurCharge" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
Dhlc2B:
```

```
<xs:complexType name="tWeight4">
  <xs:simpleContent>
    <xs:extension base="tWeightValue">
      <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="150" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume4">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

```
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="0.535" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiver4">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues4">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="GoodsValue" type="General:tGoodsValue" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptions4">
  <xs:sequence>
    <xs:element name="Guarantee" type="General:tGuarantee" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdvice" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdviceComType" type="General:tComType" maxOccurs="1" minOccurs="0" />
    <xs:element name="DeliveryAdvice" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="InCarriage" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="RecPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="ThirdPtyPays" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="COD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="Insurance" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="LQ_DangerousGoods" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="DeliveryWithoutPOD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="PickupAtTerminal" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

5.2.13 Xml schema for DkEuroConnect

```
<xs:complexType name="tDkEuroConnect">
  <xs:sequence>
    <xs:element name="AgreementNo" type="EuroConnect:tAgreementNo_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="EuroConnect:tSenderReceiver_EC" maxOccurs="1" minOccurs="1" />
    <xs:element name="Dimensions" type="EuroConnect:tDimensions" maxOccurs="1" minOccurs="0" />
    <xs:element name="Options" type="EuroConnect:tOptions9" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

```
<xs:element name="OwnSurCharge" type="General:tOwnSurCharge" maxOccurs="1" minOccurs="0"
/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="tSenderReceiver_EC">
  <xs:sequence>
    <xs:element name="ImportExport" type="tImportExport" maxOccurs="1" minOccurs="1" />
    <xs:element name="FromCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1"
  " />
    <xs:element name="FromPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1"
  />
    <xs:element name="ToPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tDimensions">
  <xs:sequence>
    <xs:element name="Weight" type="tWeight_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="tVolume_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Loadingmeter" type="tLoadingmeter_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Length" type="tLength_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Width" type="tWidth_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Height" type="tHeight_EC" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="tAgreementNo_EC">
  <xs:restriction base="xs:string">
    <xs:pattern value="\d{0,8}" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tImportExport">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="I" />
    <xs:enumeration value="E" />
    <xs:enumeration value="D" />
    <xs:enumeration value="ED" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tPostalCode_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="6" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWeight_EC">
  <xs:simpleContent>
    <xs:extension base="tWeightValue_EC">
      <xs:attribute name="unit" type="tWeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue_EC">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999900" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="kg" />
  </xs:restriction>
</xs:simpleType>
```



```

<xs:complexType name="tVolume_EC">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue_EC">
      <xs:attribute name="unit" type="tVolumeUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tVolumeUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeter_EC">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue_EC" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.9" />
    <xs:fractionDigits value="1" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLength_EC">
  <xs:simpleContent>
    <xs:extension base="tLengthValue_EC">
      <xs:attribute name="unit" type="tLengthUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tLengthUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth_EC">
  <xs:simpleContent>
    <xs:extension base="tWidthValue_EC">
      <xs:attribute name="unit" type="tWidthUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>

```

```

<xs:simpleType name="tWidthUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="cm" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tHeight_EC">
  <xs:simpleContent>
    <xs:extension base="tHeightValue_EC">
      <xs:attribute name="unit" type="tHeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tHeightValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tHeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="cm" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCombiterms_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCOD_EC">
  <xs:simpleContent>
    <xs:extension base="tCODValue_EC">
      <xs:attribute name="currency" type="tCODCurrency_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tCODValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCODCurrency_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tInsurance_EC">
  <xs:simpleContent>
    <xs:extension base="tInsuranceValue_EC">
      <xs:attribute name="currency" type="tInsuranceCurrency_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tInsuranceValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tInsuranceCurrency_EC">
  <xs:restriction base="xs:string">

```

```

        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfPallets_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfItems_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999999" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tOptions9">
    <xs:sequence>
        <xs:element name="Combiterm" type="tCombiterms_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="COD" type="tCOD_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="DangerousGoods" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="Insurance" type="tInsurance_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfPallets" type="tNoOfPallets_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfItems" type="tNoOfItems_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>

```

5.2.14 Xml schema for DkEuroConnectDomestic

```

<xs:complexType name="tDkEuroConnectDomestic">
    <xs:sequence>
        <xs:element name="AgreementNo" type="EuroConnect:tAgreementNo_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="SenderReceiver" type="EuroConnect:tSenderReceiver_EC" maxOccurs="1" minOccurs="1" />
        <xs:element name="Dimensions" type="EuroConnect:tDimensions" maxOccurs="1" minOccurs="0" />
        <xs:element name="Options" type="EuroConnect:tOptions9" maxOccurs="1" minOccurs="0" />
        <xs:element name="OwnSurCharge" type="General:tOwnSurCharge" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="tSenderReceiver_EC">
    <xs:sequence>
        <xs:element name="ImportExport" type="tImportExport" maxOccurs="1" minOccurs="1" />
        <xs:element name="FromCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
        <xs:element name="FromPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
        <xs:element name="ToPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tDimensions">
    <xs:sequence>
        <xs:element name="Weight" type="tWeight_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Volume" type="tVolume_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Loadingmeter" type="tLoadingmeter_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Length" type="tLength_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Width" type="tWidth_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="Height" type="tHeight_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>

```

```

    </xs:sequence>
</xs:complexType>
<xs:simpleType name="tAgreementNo_EC">
  <xs:restriction base="xs:string">
    <xs:pattern value="\d{0,8}" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tImportExport">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="I" />
    <xs:enumeration value="E" />
    <xs:enumeration value="D" />
    <xs:enumeration value="ED" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tPostalCode_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="6" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWeight_EC">
  <xs:simpleContent>
    <xs:extension base="tWeightValue_EC">
      <xs:attribute name="unit" type="tWeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue_EC">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999900" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="kg" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume_EC">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue_EC">
      <xs:attribute name="unit" type="tVolumeUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tVolumeUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeter_EC">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue_EC" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue_EC">
  <xs:restriction base="xs:decimal">

```

```

        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999.9" />
        <xs:fractionDigits value="1" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLength_EC">
    <xs:simpleContent>
        <xs:extension base="tLengthValue_EC">
            <xs:attribute name="unit" type="tLengthUnit_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tLengthUnit_EC">
    <xs:restriction base="xs:string">
        <xs:enumeration value="m" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth_EC">
    <xs:simpleContent>
        <xs:extension base="tWidthValue_EC">
            <xs:attribute name="unit" type="tWidthUnit_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWidthUnit_EC">
    <xs:restriction base="xs:string">
        <xs:enumeration value="cm" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tHeight_EC">
    <xs:simpleContent>
        <xs:extension base="tHeightValue_EC">
            <xs:attribute name="unit" type="tHeightUnit_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tHeightValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tHeightUnit_EC">
    <xs:restriction base="xs:string">
        <xs:enumeration value="cm" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCombiterms_EC">
    <xs:restriction base="xs:string">

```

```

        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCOD_EC">
    <xs:simpleContent>
        <xs:extension base="tCODValue_EC">
            <xs:attribute name="currency" type="tCODCurrency_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tCODValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCODCurrency_EC">
    <xs:restriction base="xs:string">
        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tInsurance_EC">
    <xs:simpleContent>
        <xs:extension base="tInsuranceValue_EC">
            <xs:attribute name="currency" type="tInsuranceCurrency_EC" use="required" />
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tInsuranceValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tInsuranceCurrency_EC">
    <xs:restriction base="xs:string">
        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfPallets_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfItems_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999999" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tOptions9">
    <xs:sequence>
        <xs:element name="Combiterm" type="tCombiterms_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="COD" type="tCOD_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="DangerousGoods" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="Insurance" type="tInsurance_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfPallets" type="tNoOfPallets_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfItems" type="tNoOfItems_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>

```

5.2.15 Xml schema for DkEuroLineDomestic

```
<xs:complexType name="tDkEuroLineDomestic">
  <xs:sequence>
    <xs:element name="AgreementNo" type="EuroConnect:tAgreementNo_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="SenderReceiver" type="EuroConnect:tSenderReceiver_EC" maxOccurs="1" minOccurs="1" />
    <xs:element name="Dimensions" type="EuroConnect:tDimensions" maxOccurs="1" minOccurs="0" />
    <xs:element name="Options" type="EuroConnect:tOptions9" maxOccurs="1" minOccurs="0" />
    <xs:element name="OwnSurCharge" type="General:tOwnSurCharge" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="tSenderReceiver_EC">
  <xs:sequence>
    <xs:element name="ImportExport" type="tImportExport" maxOccurs="1" minOccurs="1" />
    <xs:element name="FromCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
    <xs:element name="FromPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
    <xs:element name="ToPostCode" type="tPostalCode_EC" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="tDimensions">
  <xs:sequence>
    <xs:element name="Weight" type="tWeight_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Volume" type="tVolume_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Loadingmeter" type="tLoadingmeter_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Length" type="tLength_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Width" type="tWidth_EC" maxOccurs="1" minOccurs="0" />
    <xs:element name="Height" type="tHeight_EC" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

<xs:simpleType name="tAgreementNo_EC">
  <xs:restriction base="xs:string">
    <xs:pattern value="\d{0,8}" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="tImportExport">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="I" />
    <xs:enumeration value="E" />
    <xs:enumeration value="D" />
    <xs:enumeration value="ED" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="tPostalCode_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="6" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="tWeight_EC">
  <xs:simpleContent>
    <xs:extension base="tWeightValue_EC">
      <xs:attribute name="unit" type="tWeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

```

    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue_EC">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999900" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="kg" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume_EC">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue_EC">
      <xs:attribute name="unit" type="tVolumeUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tVolumeUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeter_EC">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue_EC" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999.9" />
    <xs:fractionDigits value="1" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLength_EC">
  <xs:simpleContent>
    <xs:extension base="tLengthValue_EC">
      <xs:attribute name="unit" type="tLengthUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLengthValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tLengthUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWidth_EC">

```



```
<xs:simpleContent>
  <xs:extension base="tWidthValue_EC">
    <xs:attribute name="unit" type="tWidthUnit_EC" use="required" />
  </xs:extension>
</xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWidthValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWidthUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="cm" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tHeight_EC">
  <xs:simpleContent>
    <xs:extension base="tHeightValue_EC">
      <xs:attribute name="unit" type="tHeightUnit_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tHeightValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tHeightUnit_EC">
  <xs:restriction base="xs:string">
    <xs:enumeration value="cm" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCombiterms_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCOD_EC">
  <xs:simpleContent>
    <xs:extension base="tCODValue_EC">
      <xs:attribute name="currency" type="tCODCurrency_EC" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tCODValue_EC">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="999999999.99" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCODCurrency_EC">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tInsurance_EC">
  <xs:simpleContent>
    <xs:extension base="tInsuranceValue_EC">
```

```
        <xs:attribute name="currency" type="tInsuranceCurrency_EC" use="required" />
    </xs:extension>
</xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tInsuranceValue_EC">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999999.99" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tInsuranceCurrency_EC">
    <xs:restriction base="xs:string">
        <xs:maxLength value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfPallets_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfItems_EC">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="999999" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tOptions9">
    <xs:sequence>
        <xs:element name="Combiterm" type="tCombiterms_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="COD" type="tCOD_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="DangerousGoods" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="Insurance" type="tInsurance_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfPallets" type="tNoOfPallets_EC" maxOccurs="1" minOccurs="0" />
        <xs:element name="NumberOfItems" type="tNoOfItems_EC" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
```

5.2.16 Xml schema for DHLEExpress

```
<xs:complexType name="tDHLEExpress">
    <xs:sequence>
        <xs:element name="AgreementNo" type="DHLEExpress:tAgreementNo_TD" maxOccurs="1" minOccurs="0" />
        <xs:element name="SenderReceiver" type="DHLEExpress:tSenderReceiver_TD" maxOccurs="1" minOccurs="1" />
        <xs:element name="Dimensions" type="DHLEExpress:tDimensions_TD" maxOccurs="1" minOccurs="1" />
        <xs:element name="Values" type="DHLEExpress:tValues_TD" maxOccurs="1" minOccurs="1" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="tSenderReceiver_TD">
    <xs:sequence>
        <xs:element name="FromCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1" />
        <xs:element name="FromPostCode" type="tPostalCode_TD" maxOccurs="1" minOccurs="0" />
        <xs:element name="FromCity" type="tCity_TD" maxOccurs="1" minOccurs="1" />
        <xs:element name="FromSuburb" type="tCity_TD" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
```

```

    <xs:element name="ToCountryCode" type="General:tCountryCode" maxOccurs="1" minOccurs="1"
/>
    <xs:element name="ToPostCode" type="tPostalCode_TD" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToCity" type="tCity_TD" maxOccurs="1" minOccurs="1" />
    <xs:element name="ToSuburb" type="tCity_TD" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tDimensions_TD">
  <xs:sequence>
    <xs:element name="Weight" type="tWeight_TD" maxOccurs="1" minOccurs="1" />
    <xs:element name="Volume" type="tVolume_TD" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValues_TD">
  <xs:sequence>
    <xs:element name="PickupDate" type="xs:date" maxOccurs="1" minOccurs="1" />
    <xs:element name="ReadyTime" type="xs:time" maxOccurs="1" minOccurs="1" />
    <xs:element name="RTGMTOffset" type="tRTGMTOffset" maxOccurs="1" minOccurs="1" />
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    <xs:element name="CODAmount" type="tCODAmountTD" maxOccurs="1" minOccurs="0" />
    <xs:element name="CODCurCode" type="tCODCurCodeTD" maxOccurs="1" minOccurs="0" />
    <xs:element name="ServiceOpCode" type="tServiceOpCode" maxOccurs="1" minOccurs="1" />
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="tAgreementNo_TD">
  <xs:restriction base="xs:string">
    <xs:pattern value="\d{8}" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tPostalCode_TD">
  <xs:restriction base="xs:string">
    <xs:maxLength value="12" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCity_TD">
  <xs:restriction base="xs:string">
    <xs:maxLength value="45" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tWeight_TD">
  <xs:simpleContent>
    <xs:extension base="tWeightValue_TD">
      <xs:attribute name="unit" type="tWeightUnit_TD" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tWeightValue_TD">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="9999999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tWeightUnit_TD">
  <xs:restriction base="xs:string">
    <xs:enumeration value="kg" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolume_TD">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue_TD">
      <xs:attribute name="unit" type="tVolumeUnit_TD" use="required" />
    </xs:extension>
  </xs:simpleContent>

```

```
</xs:complexType>
<xs:simpleType name="tVolumeValue_TD">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="9999999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tVolumeUnit_TD">
  <xs:restriction base="xs:string">
    <xs:enumeration value="m3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCODAmountTD">
  <xs:simpleContent>
    <xs:extension base="tCODAmountValueTD" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tCODAmountValueTD">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="9999999999999.999" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCODCurCodeTD">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tServiceOpCode">
  <xs:restriction base="xs:NMTOKEN">
    <xs:enumeration value="WPX" />
    <xs:enumeration value="DOX" />
    <xs:enumeration value="TDK" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tRTGMTOffset">
  <xs:restriction base="xs:string">
    <xs:maxLength value="6" />
  </xs:restriction>
</xs:simpleType>
```

5.2.17 XML schema for DHLHomeDeliveryDHLTerminal (Product 401)

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="schDHLHomeDeliveryDhlTerminal" targetNamespace="http://www.dhl.se/schDHLHomeDelive
ryDhlTerminal.xsd" elementFormDefault="qualified" xmlns="http://www.dhl.se/schDHLHomeDelive
ryDhlTerminal.xsd" xmlns:mstns="http://www.dhl.se/schDHLHomeDeliveryDhlTerminal.xsd" xmlns:xs=
"http://www.w3.org/2001/XMLSchema" xmlns:General="http://www.dhl.se/schGeneral.xsd">
  <xs:import schemaLocation="schGeneral.xsd" namespace="http://www.dhl.se/schGeneral.xsd" />
  <xs:complexType name="tWeightHomeDelivery">
    <xs:simpleContent>
      <xs:extension base="tWeightValue">
        <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tWeightValue">
    <xs:restriction base="xs:decimal">
```

```
<xs:minInclusive value="1" />
<xs:maxInclusive value="2500" />
<xs:fractionDigits value="2" />
</xs:restriction>
</xs:simpleType>
<xs:complexType name="tVolumeHomeDelivery">
  <xs:simpleContent>
    <xs:extension base="tVolumeValue">
      <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="8.928" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeterHomeDelivery">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="1.3" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiverHomeDelivery">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
    <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValuesHomeDelivery">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptionsHomeDelivery">
  <xs:sequence>
    <xs:element name="Insurance" type="General:tInsuranceAmountSEKOption" maxOccurs="1" minOccurs="0" />
    <xs:element name="IndoorDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdviceByDriver" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="ShipmentMonitoring" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```

```
    <xs:element name="TerminalPickUp" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
</xs:schema>
```

5.2.18 XML schema for DHLHomeDeliveryDHLTerminalReturn (Product 402)

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="schDHLHomeDeliveryDhlTerminalReturn" targetNamespace="http://www.dhl.se/schDHLHomeDeliveryDhlTerminalReturn.xsd" elementFormDefault="qualified" xmlns="http://www.dhl.se/schDHLHomeDeliveryDhlTerminalReturn.xsd" xmlns:mstns="http://www.dhl.se/schDHLHomeDeliveryDhlTerminalReturn.xsd" xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:General="http://www.dhl.se/schGeneral.xsd">
  <xs:import schemaLocation="schGeneral.xsd" namespace="http://www.dhl.se/schGeneral.xsd" />
  <xs:complexType name="tWeightHomeDeliveryReturn">
    <xs:simpleContent>
      <xs:extension base="tWeightValue">
        <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tWeightValue">
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="1" />
      <xs:maxInclusive value="2500" />
      <xs:fractionDigits value="2" />
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="tVolumeHomeDeliveryReturn">
    <xs:simpleContent>
      <xs:extension base="tVolumeValue">
        <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tVolumeValue">
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="0" />
      <xs:maxInclusive value="8.928" />
      <xs:fractionDigits value="3" />
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="tLoadingmeterHomeDeliveryReturn">
    <xs:simpleContent>
      <xs:extension base="tLoadingmeterValue" />
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tLoadingmeterValue">
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="0" />
      <xs:maxInclusive value="1.3" />
      <xs:fractionDigits value="2" />
    </xs:restriction>
  </xs:simpleType>
```

```
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="tSenderReceiverHomeDeliveryReturn">
    <xs:sequence>
      <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="tValuesHomeDeliveryReturn">
    <xs:sequence>
      <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="tOptionsHomeDeliveryReturn">
    <xs:sequence>
      <xs:element name="Insurance" type="General:tInsuranceAmountSEKOption" maxOccurs="1" minOccurs="0" />
      <xs:element name="ShipmentMonitoring" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
      <xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

5.2.19 XML schema for DHLHomeDeliveryExternalTerminal (Product 501)

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="schDHLHomeDeliveryExternalTerminal" targetNamespace="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd" elementFormDefault="qualified" xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd" xmlns:mstns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd" xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:General="http://www.dhl.se/schGeneral.xsd">
  <xs:import schemaLocation="schGeneral.xsd" namespace="http://www.dhl.se/schGeneral.xsd" />
  <xs:complexType name="tWeightHomeDeliveryExternal">
    <xs:simpleContent>
      <xs:extension base="tWeightValue">
        <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tWeightValue">
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="1" />
      <xs:maxInclusive value="2500" />
      <xs:fractionDigits value="2" />
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="tVolumeHomeDeliveryExternal">
    <xs:simpleContent>
      <xs:extension base="tVolumeValue">
        <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
```

```
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="8.928" />
    <xs:fractionDigits value="3" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeterHomeDeliveryExternal">
  <xs:simpleContent>
    <xs:extension base="tLoadingmeterValue" />
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="1.3" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiverHomeDeliveryExternal">
  <xs:sequence>
    <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
    <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
    <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tValuesHomeDeliveryExternal">
  <xs:sequence>
    <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptionsHomeDeliveryExternal">
  <xs:sequence>
    <xs:element name="Insurance" type="General:tInsuranceAmountSEKOption" maxOccurs="1" minOccurs="0" />
    <xs:element name="AllocatedTimeSlot" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="IndoorDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="PreAdviceByDriver" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="TwoManDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="CarryingHelp" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="PackagingRemoval" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    <xs:element name="DisposalOfReplacedGoods" type="General:tNumberOfRepetitionsOption" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
```



```
<xs:element name="InstallationLight" type="General:tNumberOfRepetitionsOption" maxOccurs="1" minOccurs="0" />
<xs:element name="InstallationAdvanced" type="General:tNumberOfRepetitionsOption" maxOccurs="1" minOccurs="0" />
<xs:element name="Assembly20" type="General:tNumberOfRepetitionsOption" maxOccurs="1" minOccurs="0" />
<xs:element name="Assembly40" type="General:tNumberOfRepetitionsOption" maxOccurs="1" minOccurs="0" />
<xs:element name="Assembly60" type="General:tNumberOfRepetitionsOption" maxOccurs="1" minOccurs="0" />
<xs:element name="EveningDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="EveningDeliveryB" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="EveningDeliveryC" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="EveningDeliveryD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="EveningDeliveryE" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="WeekendDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="ShipmentMonitoring" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>
</xs:schema>
```

5.2.20 XML schema for DHLHomeDeliveryExternalTerminalReturn (Product 502)

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="schDHLHomeDeliveryExternalTerminalReturn" targetNamespace="http://www.dhl.se/schDHLHomeDeliveryExternalTerminalReturn.xsd" elementFormDefault="qualified" xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminalReturn.xsd" xmlns:mstns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminalReturn.xsd" xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:General="http://www.dhl.se/schGeneral.xsd">
  <xs:import schemaLocation="schGeneral.xsd" namespace="http://www.dhl.se/schGeneral.xsd" />
  <xs:complexType name="tWeightHomeDeliveryExternalReturn">
    <xs:simpleContent>
      <xs:extension base="tWeightValue">
        <xs:attribute name="unit" type="General:tWeightUnit" use="required" />
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:simpleType name="tWeightValue">
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="1" />
      <xs:maxInclusive value="2500" />
      <xs:fractionDigits value="2" />
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="tVolumeHomeDeliveryExternalReturn">
    <xs:simpleContent>
      <xs:extension base="tVolumeValue">
```

```
        <xs:attribute name="unit" type="General:tVolumeUnit" use="required" />
    </xs:extension>
</xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tVolumeValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="8.928" />
        <xs:fractionDigits value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tLoadingmeterHomeDeliveryExternalReturn">
    <xs:simpleContent>
        <xs:extension base="tLoadingmeterValue" />
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tLoadingmeterValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="1.3" />
        <xs:fractionDigits value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tSenderReceiverHomeDeliveryExternalReturn">
    <xs:sequence>
        <xs:element name="FromPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
        <xs:element name="FromCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToPostCode" type="General:tPostalCode_SE" maxOccurs="1" minOccurs="0" />
        <xs:element name="ToCity" type="General:tCity" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tValuesHomeDeliveryExternalReturn">
    <xs:sequence>
        <xs:element name="NoOfItems" type="General:tNoOfItems" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tOptionsHomeDeliveryExternalReturn">
    <xs:sequence>
        <xs:element name="Insurance" type="General:tInsuranceAmountSEKOption" maxOccurs="1" minOccurs="0" />
        <xs:element name="AllocatedTimeSlot" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="TwoManDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="CarryingHelpRemoval" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="EveningDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="EveningDeliveryB" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="EveningDeliveryC" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
        <xs:element name="EveningDeliveryD" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
```

```
<xs:element name="EveningDeliveryE" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="WeekendDelivery" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="ShipmentMonitoring" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
<xs:element name="CO2ClimateCompensation" type="xs:boolean" default="false" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>
</xs:schema>
```

5.2.21 XML schema for General

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="schGeneral" targetNamespace="http://www.dhl.se/schGeneral.xsd" elementFormDefault="qualified" xmlns="http://www.dhl.se/schGeneral.xsd" xmlns:mstns="http://www.dhl.se/schGeneral.xsd" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:simpleType name="tAgreementNo">
    <xs:restriction base="xs:string">
      <xs:pattern value="\d{6}" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tWeightUnit">
    <xs:restriction base="xs:string">
      <xs:enumeration value="kg" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tVolumeUnit">
    <xs:restriction base="xs:string">
      <xs:enumeration value="m3" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tLengthUnit">
    <xs:restriction base="xs:string">
      <xs:enumeration value="m" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tWidthUnit">
    <xs:restriction base="xs:string">
      <xs:enumeration value="cm" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tPostalCode_SE">
    <xs:restriction base="xs:string">
      <xs:pattern value="\d{5}" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tCity">
    <xs:restriction base="xs:string">
      <xs:maxLength value="20" />
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="tNoOfFullPallets">
    <xs:restriction base="xs:nonNegativeInteger">
```

```
<xs:minInclusive value="1" />
<xs:maxInclusive value="3" />
</xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfHalfPallets">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="6" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfItems">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="999" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tNoOfEURPallets">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="9999" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tSort">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="999" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tQuantity">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="1" />
    <xs:maxInclusive value="9999999" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tCODAmountSE">
  <xs:simpleContent>
    <xs:extension base="tCODValueSE">
      <xs:attribute name="currency" use="required">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:enumeration value="SEK" />
          </xs:restriction>
        </xs:simpleType>
      </xs:attribute>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tCODValueSE">
  <xs:restriction base="xs:decimal">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="9999999" />
    <xs:fractionDigits value="2" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tCountryCode">
  <xs:restriction base="xs:string">
```

```
        <xs:maxLength value="2" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tToPostCodeInt">
    <xs:restriction base="xs:string">
        <xs:maxLength value="9" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tGoodsValue">
    <xs:restriction base="xs:nonNegativeInteger">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="999999" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tGuarantee">
    <xs:restriction base="xs:NMTOKEN">
        <xs:enumeration value="None" />
        <xs:enumeration value="07" />
        <xs:enumeration value="10" />
        <xs:enumeration value="12" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tComType">
    <xs:restriction base="xs:NMTOKEN">
        <xs:enumeration value="Phone" />
        <xs:enumeration value="SMS" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tPalletPlace">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="1" />
        <xs:maxInclusive value="60" />
        <xs:fractionDigits value="1" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="tOwnSurCharge">
    <xs:sequence>
        <xs:element name="OwnSurChargePerc" type="tOwnSurChargePerc" maxOccurs="1" minOccurs="0" />
        <xs:element name="OwnSurChargeAmount" type="tOwnSurChargeAmount" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="tOwnSurChargePerc">
    <xs:simpleContent>
        <xs:extension base="tOwnSurChargePercValue">
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="tOwnSurChargePercValue">
    <xs:restriction base="xs:decimal">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="99.9" />
        <xs:fractionDigits value="1" />
    </xs:restriction>
</xs:simpleType>
```

```
<xs:simpleType name="tOwnSurChargeAmount">
  <xs:restriction base="xs:nonNegativeInteger">
    <xs:minInclusive value="0" />
    <xs:maxInclusive value="9999" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="tInsuaranceAmountSEKOption">
  <xs:sequence>
    <xs:element name="Checked" type="xs:boolean" maxOccurs="1" minOccurs="0" />
    <xs:element name="Amount" type="xs:decimal" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="tNumberOfRepetitionsOption">
  <xs:sequence>
    <xs:element name="Checked" type="xs:boolean" maxOccurs="1" minOccurs="0" />
    <xs:element name="Repetitions" type="xs:nonNegativeInteger" maxOccurs="1" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
</xs:schema>
```

6 Request example

6.1 DHLStycke SOAP:Envelope

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QuoteForPrice xmlns="http://www.dhl.se/">
      <Credentials xmlns="http://www.dhl.se/schCredentials.xsd">
        <User>XXXX</User>
        <Password>XXXX</Password>
      </Credentials>
      <Quote xmlns="http://www.dhl.se/schQuote.xsd">
        <DHLStycke>
          <AgreementNo>123456</AgreementNo>
          <Weight unit="kg">7.5</Weight>
          <Volume unit="m3">0.82</Volume>
          <Loadingmeter>1.1</Loadingmeter>
          <SenderReceiver>
            <FromPostCode
xmlns="http://www.dhl.se/schDHLStycke.xsd">55116</FromPostCode>
            <FromCity xmlns="http://www.dhl.se/schDHLStycke.xsd" />
            <ToPostCode xmlns="http://www.dhl.se/schDHLStycke.xsd">56432</ToPostCode>
            <ToCity xmlns="http://www.dhl.se/schDHLStycke.xsd" />
          </SenderReceiver>
          <Values>
            <NoOfItems xmlns="http://www.dhl.se/schDHLStycke.xsd">1</NoOfItems>
          </Values>
          <Options>
            <Dangerous xmlns="http://www.dhl.se/schDHLStycke.xsd">true</Dangerous>
            <Guarantee xmlns="http://www.dhl.se/schDHLStycke.xsd">10</Guarantee>
            <Warm xmlns="http://www.dhl.se/schDHLStycke.xsd">true</Warm>
          </Options>
        </DHLStycke>
      </Quote>
    </QuoteForPrice>
  </soap:Body>
</soap:Envelope>
```

```
        </DHLStycke>
    </Quote>
</QuoteForPrice>
</soap:Body>
</soap:Envelope>
```

6.2 DHLHomeDeliveryExternalTerminal SOAP:Envelope example

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QuoteForPriceForModuleCountry xmlns="http://www.dhl.se/">
      <Credentials xmlns="http://www.dhl.se/schCredentials.xsd">
        <User>XXXX</User>
        <Password>XXXX</Password>
      </Credentials>
      <Quote xmlns="http://www.dhl.se/schQuote.xsd">
        <DHLHomeDeliveryExternalTerminal>
          <AgreementNo>000000</AgreementNo>
          <Weight unit="kg">12</Weight>
          <Volume unit="m3">0</Volume>
          <Loadingmeter>0</Loadingmeter>
          <SenderReceiver>
            <FromPostCode xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">17000</FromPostCode>
            <FromCity xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">SOLNA</FromCity>
            <ToPostCode xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">75002</ToPostCode>
            <ToCity xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">UPPSALA</ToCity>
          </SenderReceiver>
          <Values>
            <NoOfItems xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">2</NoOfItems>
          </Values>
          <Options>
            <Insurance xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
              <Checked xmlns="http://www.dhl.se/schGeneral.xsd">>false</Checked>
              <Amount xmlns="http://www.dhl.se/schGeneral.xsd">0</Amount>
            </Insurance>
            <IndoorDelivery xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">>true</IndoorDelivery>
            <PreAdviceByDriver xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">true</PreAdviceByDriver>
            <DisposalOfReplacedGoods xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
              <Checked xmlns="http://www.dhl.se/schGeneral.xsd">>true</Checked>
              <Repetitions xmlns="http://www.dhl.se/schGeneral.xsd">2</Repetitions>
            </DisposalOfReplacedGoods>
            <InstallationLight xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
              <Checked xmlns="http://www.dhl.se/schGeneral.xsd">>true</Checked>
```

```
<Repetitions xmlns="http://www.dhl.se/schGeneral.xsd">1</Repetitions>
</InstallationLight>
<InstallationAdvanced xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.
xsd">
  <Checked xmlns="http://www.dhl.se/schGeneral.xsd">false</Checked>
  <Repetitions xmlns="http://www.dhl.se/schGeneral.xsd">0</Repetitions>
</InstallationAdvanced>
<Assembly20 xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
  <Checked xmlns="http://www.dhl.se/schGeneral.xsd">>true</Checked>
  <Repetitions xmlns="http://www.dhl.se/schGeneral.xsd">1</Repetitions>
</Assembly20>
<Assembly40 xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
  <Checked xmlns="http://www.dhl.se/schGeneral.xsd">false</Checked>
  <Repetitions xmlns="http://www.dhl.se/schGeneral.xsd">0</Repetitions>
</Assembly40>
<Assembly60 xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
  <Checked xmlns="http://www.dhl.se/schGeneral.xsd">false</Checked>
  <Repetitions xmlns="http://www.dhl.se/schGeneral.xsd">0</Repetitions>
</Assembly60>
<EveningDelivery xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xsd">
true</EveningDelivery>
  <ShipmentMonitoring xmlns="http://www.dhl.se/schDHLHomeDeliveryExternalTerminal.xs
d">true</ShipmentMonitoring>
  </Options>
  <OwnSurCharge>
    <OwnSurChargePerc xmlns="http://www.dhl.se/schGeneral.xsd">10</OwnSurChargePerc>
    <OwnSurChargeAmount xmlns="http://www.dhl.se/schGeneral.xsd">0</OwnSurChargeAmount
>
  </OwnSurCharge>
</DHLHomeDeliveryExternalTerminal>
</Quote>
<strCountryCode>SE</strCountryCode>
</QuoteForPriceForModuleCountry>
</soap:Body>
</soap:Envelope>
```

6.3 DHL Parti SOAP:Envelope example

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsi="http://www.w3
.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QuoteForPriceForModuleCountry xmlns="http://www.dhl.se/">
      <Credentials xmlns="http://www.dhl.se/schCredentials.xsd" />
      <Quote xmlns="http://www.dhl.se/schQuote.xsd">
        <DHLParti>
          <SortAndQuantitySelected>false</SortAndQuantitySelected>
          <Weight unit="kg">50</Weight>
          <SenderReceiver>
            <FromPostCode xmlns="http://www.dhl.se/schDHLParti.xsd">17000</FromPostCode>
            <FromCity xmlns="http://www.dhl.se/schDHLParti.xsd">SOLNA</FromCity>
            <ToPostCode xmlns="http://www.dhl.se/schDHLParti.xsd">55473</ToPostCode>
            <ToCity xmlns="http://www.dhl.se/schDHLParti.xsd">JÖNKÖPING</ToCity>
          </SenderReceiver>
          <Values>
```



```
<NoOfItems xmlns="http://www.dhl.se/schDHLParti.xsd">15</NoOfItems>  
<GoodsValue xmlns="http://www.dhl.se/schDHLParti.xsd">1000</GoodsValue>  
</Values>  
<Options>  
<DeliveryAdvice xmlns="http://www.dhl.se/schDHLParti.xsd">true</DeliveryAdvice>  
<Insurance xmlns="http://www.dhl.se/schDHLParti.xsd">true</Insurance>  
</Options>  
<OwnSurCharge />  
</DHLParti>  
</Quote>  
<strCountryCode>SE</strCountryCode>  
</QuoteForPriceForModuleCountry>  
</soap:Body>  
</soap:Envelope>
```